

Jet countertop

Elegant and compact unit for busy environments



A compact reliable countertop unit

The Jet countertop system facilitates workplace hydration while remaining elegant, compact and functional. This is particularly helpful in situations where space is limited but a larger quantity of drinking water is required. The Jet counter top is a functional water dispenser and perfectly suited to most medium volume locations.

Leading technology

The Jet countertop features two core technologies:



Performance filtration

Professional grade filters are used to improve taste and reduce odours resulting in great-tasting, crystal-clear water.



Ice bank cooling system

Ice bank cooling technology is a necessity in busy environments where large quantities of consistently ice-cold water are required.









Professional water dispensing for commercial environments

The Jet countertop is the recommended space saving solution for environments with a medium volume of traffic, such as busy offices, professional studios, small catering facilities or conference centres.

Features

- Compact design suitable to fit a variety of worktops
- Four water dispensing options - cold, ambient, sparkling and hot
- Integrated drip tray to collect any spills
- Safety valve prevents accidental water leakage
- Large dispense area ideal for filling different sized containers
- High volume machine suitable for workplace environments with medium to high footfall
- Easy to use push button dispense
- Optional electronic controls

Water options

	cold	sparkling	ambient	hot	extra hot
1					
2					
3					

Technical specifications

Types available

Countertop

Dimensions

280 mm (W) x 405 mm (H) x 520 mm (D)

Dispensing area height

270 mm

Weight

Cold, ambient 30L: 21 KG

Cold, ambient & hot 30L: 23 KG

Cold, ambient & sparkling 30L: 26 KG

Standard filtration supplied

Carbon

Dispensing capacity

30L/h

Compressor

Compressor (R134a gas) 230v - 50Hz (360 kcal/h)

Water temperatures settings

Cold: 10°C



Call us today

Waterlogic UK

+ 44 (0) 333 600 1845

enquiries@waterlogic.co.uk

www.waterlogic.co.uk

Waterlogic IRE

1800 266 537

info@waterlogic.ie

www.waterlogic.ie

Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.